



COMPACT LONG-RANGE HD MULTI-SPECTRAL SURVEILLANCE SYSTEM

TacFLIR® 230

The TacFLIR® 230 provides maximum sensor range performance including a high-resolution color zoom TV camera with low light capability, a powerful 640 x 480 cooled MWIR thermal camera with 18x total magnification, and optional laser pointer and rangefinder. At 41 pounds and with a nine-inch diameter, the TacFLIR 230 provides the ability to deploy on any platform including UGVs.

Optimized for vehicle operations, TacFLIR 230 is tailored through extensive operational experience for RECCE, force protection, ISR, commander's viewer, driver's vision, and situational awareness. It's easily deployed with extendable masts and gyro-stabilized for on-the-move operations. TacFLIR 230's multi-sensor payload provides crisp, stable imagery through total darkness and smoke while on the move. Qualified and rugged, it's built to MIL-STD-461, MIL-STD-810, and MIL-STD-704E.

FEATURES

OPTIMIZED FOR MOBILITY

Easily deployed with extendable masts and tailored through extensive vehicle experience for RECCE, force protection, driver's vision and situational awareness.

STABILIZED FOR ON-THE-MOVE OPERATION

Gyro-stabilized for mid-range ISR and tuned for vehicle installation, TacFLIR 230 provides maximum sensor range performance over typical pan/tilt systems.

MULTI-SENSOR SYSTEM

High-res color camera; powerful 640 x 480 cooled MWIR thermal camera with 18x total zoom; optional laser rangefinder and/or pointer.

FULLY INTEGRATED TO VEHICLE

TacFLIR 230 communicates with vehicle systems, GPS, INS, radar, and Moving Map.

ERGONOMIC HAND CONTROLLER

Ruggedized control unit is backlit, NVIS compatible, and fully sealed.

APPLICATIONS

RECONNAISSANCE

SURVEILLANCE

MILITARY POLICE SECURITY

FORWARD OBSERVATION

FORCE PROTECTION

SPECIFICATIONS

Thermal Imager	
Sensor type	Indium Antimonide Focal Plane Array (MWIR)
Zoom Ratio	10x continuous zoom
Image Resolution	640 x 480
Optional Zoom Extender	1.8 x
Daylight/Color CCD TV	
Performance	Long range optics with maximized focal lengths
Zoom	30x continuous
Low light	0.7 lux
Autotracker	
Performance	Multimode video autotracker
Laser Range Finder	
Type	Class 1 eye-safe
Range	10 km (15 km on large targets)
Typical Range Accuracy	+/- 5 m
Laser Pointer	
Nominal Wavelength	852 nm
Power	30 mW nominal
Classification	Class 3B (per ANSI Z136.1-2007)
Mechanical/Electrical	
System Weight	~41 lbs (~18.5 kg)
Stabilized Gimbal Assembly (SGA)	13" d x 15.5" h (330 mm x 394 mm), cylindrical volume 360° AZ continuous, +60° to -60° EL
Interfaces	RS-232, RS-422, Analog (NTSC & PAL)
Power	18-30 VDC
Environmental	
Standards	MIL-STD-461, MIL-STD-810, MIL-STD-704E
Ergonomic, Ruggedized Control Unit Options	
Backlit, hand control unit NVIS compatible and fully sealed design (HCU)	



AMERICAS
CORPORATE
HEADQUARTERS
FLIR Systems Inc.
27700 SW Parkway Ave
Wilsonville OR 97070
+1 877.773.3547

Washington DC
2800 Crystal Drive
Suite 330
Arlington, VA 22202
PH: +1.703.416.6666

EUROPE

FLIR Systems
2 Kings Hill Avenue - Kings Hill
West Malling, Kent ME19 4AQ
United Kingdom
PH: +44 (0)1732 220 011
F +44 (0)1732 843 707

FLIR Systems AB
Antennvägen 6,
PO Box 737
SE-187 66 Täby
Sweden
PH: +46 (0)8 753 25 00

MIDDLE EAST

FLIR Systems B.V. - Abu Dhabi
Wadi Al Fey St.
Building 60, Office # 302
New Ministries Exit / Khalifa Park
Area
Abu Dhabi, U.A.E.
Office: +971 2 666 1561
e-Fax +1 503 914 1591

FLIR Systems Saudi Arabia
Office 127, First Floor
Akaria Plaza Building, Olaya Street
Riyadh, 11481, Saudi Arabia
Office: +966 11 464 5323
Fax +966 11 464 0438

ASIA

FLIR Systems Japan K.K.
Meguro Tokyu Bldg. 5F,
2-13-17
Kami-Osaki, Shinaga-
wa-ku.
Tokyo, 141-0021, Japan
T +81-3-6721-6648



For More Information contact
surveillance_sales@flir.com

www.flir.com
NASDAQ: FLIR

Equipment described herein is
subject to US export regulations
and may require a license prior
to export. Diversion contrary to
US law is prohibited. Imagery
for illustration purposes only.
Specifications are subject to
change without notice. ©2018
FLIR Systems, Inc. All rights
reserved. 08/08/18

18-0682-SUR-TacFLIR 230 HD



The World's Sixth Sense®