



COMPACT LONG-RANGE HD MULTI-SPECTRAL SURVEILLANCE SYSTEM

TacFLIR® 280-HD

TacFLIR® 280-HD is a high-performance land-based imaging system designed to identify and track smugglers, terrorists, or any other threat – day and night, and in the toughest terrain. Tailored for mobile deployment with high-definition imaging and powerful optics, TacFLIR 280-HD reveals the details necessary for long-range vehicle detection, identification, and threat assessment. In fact, the long-range performance allows operators longer standoff to detect and identify targets.

Optimized for vehicle operations, gyro-stabilized TacFLIR 280-HD provides crisp, stable imagery through total darkness and smoke while on the move. Qualified and rugged, it's built to MIL-STD-461 and MIL-STD-810. Customize payload with multiple options, including CCD or SWIR spotter scope, laser illuminator, and laser pointer. Internal navigation system and laser rangefinder provide accurate target location coordinates to pinpoint areas of interest and support precision tracking solutions for all sensors.

FEATURES

HD EXTENDED RANGE THERMAL IMAGING

720 InSb IR focal plane array detects and identifies targets at longer standoff and with higher resolution. 640 also available.

CONTINUOUS ZOOM DAY/LOW-LIGHT CAMERA

HD sensors with 20x continuous zoom and 120x total magnification produce vivid colors and superior night visibility.

EYESAFE LASER RANGEFINDER

Accurately determine range to target and geo-location for fire control calculations. Optional NIR and SWIR laser pointer and illuminator available.

INTERNAL NAVIGATION SYSTEM

Embedded INS determines and disseminates accurate target location coordinates.

TAILORED FOR MOBILE APPLICATIONS

Rugged and gyro-stabilized to provide crisp imagery even while on the move, TacFLIR 280-HD detects and assesses threats a full 360° area.

APPLICATIONS

RECONNAISSANCE

SURVEILLANCE

MILITARY POLICE SECURITY

FORWARD OBSERVATION

FORCE PROTECTION

SPECIFICATIONS

Thermal Imager	
Sensor type	1280x720 InSb FPA (640 x 480 optional)
Wavelength	3-5 µm
FOVs	Optical: 40°-2° continuous 4X E-Zoom: 0.5°
Daylight Camera	
Sensor type	1920x1080 CCD
FOVs	Optical: 54.4° to 1.5° 3X E-Zoom: 0.5°
Low Light Camera	
Sensor type	1280x720 sCMOS
FOVs	Optical: 52.1° to 1.4° 3X E-Zoom: 0.5°
Spotter Scope (Option)	
Sensor type	1920x1080 CCD or 640x480 SWIR
FOVs	CCD: 29.9°, 4.83°, 0.92°, 0.51° (0.25° w/2X E-Zoom) SWIR: 32.8°, 5.32°, 1.01°, 0.56° (0.28° w/2X E-Zoom)
Laser Payloads	
Rangefinder	Max Range: 30 km Classification: Class 1 or Class 1M (10 Hz)
Illuminator (Option)	Power: 1 W or 2 W – NIR or SWIR Classification: Class 4
Pointer (Option)	Power: 150 mW Classification: Class 3b
System Performance	
System type	Gyro stabilized TFU w/ seperate CEU
Az. coverage	360°
System Interfaces	
Digital video	SMPTE 292M/HDMI
Analog video	NTSC/PAL
Control	RS-232, RS-422
Data	RS-232, RS-422
Environmental	
Standards	MIL-STD-810, MIL-STD-461
Operating temperature	-40°C to 55°C
Power Requirements	
Voltage	24VDC
Consumption 2	240 W Typical, 350 W Max
Anti-Ice	Additional 360 W

Dimensions & Weight

TFU size	14"(d) x 16"(h) cylindrical volume
TFU weight	<55 lbs
CEU size	12.0 w x 12.0 d x 5.5 h
CEU weight	<19 lb

Other Options & Accessories

Displays & Recorders, 3rd Party Video Processing



AMERICAS

FLIR Systems, Inc.
Corporate Headquarters
27700 SW Parkway Ave
Wilsonville, OR 97070
Office: +1 877.773.3547

FLIR Systems, Inc.
DC Headquarters
1201 S. Joyce Street
Suite C006
Arlington, VA 22202
Office: +1 703.682.3400

EUROPE

FLIR Systems
2 Kings Hill Avenue - Kings Hill
West Malling, Kent ME19 4AQ
United Kingdom
Office: +44 (0)1732 220 011
Fax: +44 (0)1732 843 707

FLIR Systems AB
Antennvägen 6,
PO Box 737
SE-187 66 Täby
Sweden
Office: +46 (0)8 753 25 00

MIDDLE EAST

FLIR Systems B.V. - Abu Dhabi
Wadi Al Fey St.
Building 60, Office # 302
New Ministries Exit / Khalifa Park Area
Abu Dhabi, U.A.E.
Office: +971 2 666 1561
e-Fax: +1 503 914 1591

FLIR Systems Saudi Arabia
Office 127, First Floor
Akaria Plaza Building, Olaya Street
Riyadh, 11481, Saudi Arabia
Office: +966 11 464 5323
Fax: +966 11 464 0438

ASIA

FLIR Systems Japan K.K.
Meguro Tokyu Bldg. 5F,
2-13-17
Kami-Osaki, Shinagawa-ku.
Tokyo, 141-0021, Japan
Office: +81-3-6721-6648



For More Information contact
surveillance_sales@flir.com

www.flir.com
NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2019 FLIR Systems, Inc. All rights reserved. 03/04/19

19-0525-SUR-TacFLIR280-HD SS LTR



The World's Sixth Sense®